


SPECIFICATIONS

Dallas Specialty Flexible PVC Pipe Coupling

Part# **DS02-108**

**FITS: 10" CLAY PIPE x 8" CI/PVC part assembled with
(1) Flexible PVC Bushing to accommodate 8" CI/PVC**



Coupling ID Specifications

A SIDE (ID)	B SIDE (ID)	C SIDE HEIGHT
8.50"	12.25"	6.50"



Max Temp	140 degree F
Min Temp	-30 degree F
Pressure	Non-Pressure
Material	60/EPDM Rubber
Cplg Wall Thickness	1/2"

Install Torque	60in-lb torque
Meets ASTM	C1173 / D5926
Case Quantity	2 pc
Band Series	300 Series SS
Clamps	(1)DS-200 & (1)DS-188

COUPLING & Bushing(s)

- Manufactured in the USA
- Meeting Material Requirements of IPC®/IRC®
- cUPC® Canadian Standards
- ASTM C-1173 D-5926
- Sporadic Temperature Rating 140°
- Maximum Test Pressure 4.3 PSI

Clamps

- 1/2" Width/AISI 301 SS
- Torque: 60in-lb Installation Torque
- Band Screw: 5/16" Hex Head AISI 305SS
- Band Housing: AISI 301SS
- Meets Requirements: SAE J1670



Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ± 3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS
SPECIALTY
& MFG CO.**

1161 RUGGLE ST. GRAND PRAIRIE, TX 75050

P: 972-641-8444 • 800-222-5644 • F: 972-641-8488

Email: ds@dalspc.com • www.dallasspecialty.com