


# SPECIFICATIONS

## Dallas Specialty Lg. Diameter Flexible Pipe Coupling for Sewer & Drain applications



Part# **DS06R-1515**

FITS: 15"RCP Reinforced Concrete Pipe x 15" CI/PVC Pipe  
Part assembled with flexible bushings for reduction to 15"CI/PVC



Coupling Made to ID Specifications

A SIDE (ID)	B SIDE (ID)	C SIDE HEIGHT
19.75"	15.40"	8.00"

Picture may not represent part # listed here as some couplings may be reducing sized couplings with reduction on the exterior of the coupling



Constant Tension Banding used on all 27" & larger couplings providing 80"lb torque

Max Temp	140°degree F
Min Temp	-30°degree F
Pressure	Non-Pressure
Material	60/EPDM Rubber
Coupling Wall Thickness	1/2"

Install Torque	80in-lb torque
Meets ASTM	C1173 / D5926
Case Quantity	1 pc
Band Series	301SS/304SS Series SS
Clamps	Constant Tension Bands

### COUPLING & Bushing(s)

- Manufactured in the USA
- Meeting Material Requirements of IPC<sup>®</sup> / IRC<sup>®</sup>
- cUPC<sup>®</sup> Meets Canadian Standards
- ASTM C-1173 D-5926
- Sporadic Temperature Rating 140°
- Maximum Test Pressure 4.3 PSI



### Clamps

- Constant Tension Bands: Qty4 bands 1/2"Width AISI 301SS
- CT Band: Torque: 80in-lb Install Torque
- Band Screw: 3/8"Hex Head AISI 301SS
- Band Housing: AISI 304SS
- Meets Requirements: SAE J1670

Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ±3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS  
SPECIALTY  
& MFG CO.**

1161 RUGGLE ST. GRAND PRAIRIE, TX 75050  
P: 972-641-8444 • 800-222-5644 • F: 972-641-8488  
Email: ds@dalspc.com • [www.dallasspecialty.com](http://www.dallasspecialty.com)