

DS109CSC

DALLAS SPECIALTY Economy Size Round Single Outlet Valve Box with Lid marked CSC (City Side Cleanout) Dimensions: 6-1/4"Diameter x 9"Deep

Case Quantity 36/case

Pallet Quantity 720pc (20cases)

Mfg'd in the USA

BOX

MODEL# DS109B ASSEMBLED WITH LID #DS109CSCL

Body accommodates Dallas Specialty Flush Snap-down Lids

MATERIAL: HD POLYPROPYLENE

DIMENSIONS: TOP 6-1/4"ID x 6-1/2"OD / **BASE** 7-1/2"ID x 7-3/4"OD

OUTLETS: SINGLE OUTLET SIZED 2-1/2"

SPECS: ASTM

BOX ADDITIONS/COMPATIBILITY: Body is standard economy box without alterations or additions. Lid's available in a variety of colors & configurations, including solid cast iron round lids available for light traffic areas

LID

MODEL# DS109CSCL ASSEMBLED ON #DS109B STANDARD BODY

MATERIAL: HD POLYPROPYLENE

LID DIMENSIONS/FLUSH FIT SNAP-DOWN: 6-1/2"OD x 1-1/2"THICKNESS

COLOR: GREEN - FOR YARDS, PLANTERS, PARKWAYS, GRASS AREAS, GOLF COURSES, OR IRRIGATION VALVE APPLICATIONS

FIT: FLUSH STYLE / FITS TIGHT WITH SNAP DOWN TABS (OVERLAPPING STYLE LID)

REMOVE LID USING 1" FINGER HOLE ON TOP OF LID

MARKINGS: STANDARD MFG MARKINGS & IDENTIFICATION
CUSTOM MARKINGS AVAILABLE & LOGOS (SUCH AS CSC) AS MADE

SPECS: ASTM

LID ADDITION OPTIONS: LIDS AVAILABLE IN GREEN, PURPLE, BLACK, TAN, BLUE AND AVAILABLE WITH A VARIETY OF MARKINGS SUCH AS WATER, RECLAIMED WATER, NO MARKINGS (BLANK) AND OTHER MARKINGS. PLEASE CONSULT WITH YOUR DALLAS SPECIALTY REPRESENTATIVE



PROPERTIES / TEST VALUES

Tensile Strength: 3480 PSI

Density: 0.918

Durometer Shore D0.825

Flexural Strength: 255-300 PSI

Minimal Wall Dim: 0.250"

Deflection Temp: 200 F at 66 psi

IZOD IN 23C: 1.05 ft lbs/in

IZOD IUN 18C: 5.3 ft lbs/in