

DS1200IBLUWTRH

DALLAS SPECIALTY RECTANGULAR VALVE BOX - 17"WIDE x 12"LONG x 12"DEEP
PALLET QTY / 72pc MFG'D IN THE USA

BOX

MODEL # DS1200B BODY - ASSEMBLED WITH DS1200IBLUEL (BLUE LID)

DIMENSIONS: Top: 17-1/8"W x 11-7/8"L (OD) x 12"Deep

Base: 21"W x 16-5/8"L (OD)

WITH 2" TOUCH READ HOLE (FOR AUTOMATIC TOUCH READ DEVICE). BOX ACCOMODATES FLUSH OR OVERLAPPING STYLE DS LIDS

MATERIAL: HEAVY DUTY POLYPROPYLENE / MADE FOR YARDS & PLANTERS WHERE ONLY LIGHT FOOT TRAFFIC EXISTS

OUTLETS: SINGLE / 2-3/4" - PIPE SLOT

SPECS: ASTM

BOX ADDITIONS/COMPATIBILITY: ACCEPTS ALL DALLAS SPECIALTY DS1200 STYLE LIDS &/OR DS600EXT 6"EXTENSION BOXES

LID

MODEL# DS1200IBLUEL ASSEMBLED ON DS1200B (SINGLE OUTLET BOX)

FOR ASSEMBLY ON DS1200B BOX BODIES OR DS600EXT

DIMENSIONS: 15-3/8"W x 10-1/8"L (OD) x 1-3/4"thickness

MATERIAL: POLYPROPYLENE

COLOR: BLUE (USED IN YARDS, PLANTERS, PARKWAYS, GRASSY AREAS, GOLF COURSES, AND/OR VALVE & IRRIGATION CONTROLS APPLICATIONS)

FIT: FLUSH STYLE / FITS TIGHT WITH SNAP DOWN TABS

LID REMOVAL: USING 1"HOLE ON TOP OF LID

MARKINGS: STANDARD MFG MARKINGS & IDENTIFICATION CUSTOM MARKINGS AVAILABLE & LOGOS

SPECS: ASTM

LID ADDITION OPTIONS: 2" TOUCH READ HOLE, AND/OR AMR BRACKET ATTACHMENT, AND/OR SOCKET BOLT LOCK



PROPERTIES / TEST VALUES

Tensile Strength: 3480 PSI

Density: 0.918

Durometer Shore D0.825

Flexural Strength: 255-300 PSI

Minimal Wall Dim: 0.250"

Deflection Temp: 200 F at 66 psi

IZOD IN 23C: 1.05 ft lbs/in

IZOD IUN 18C: 5.3 ft lbs/in



ds® **DALLAS SPECIALTY & MFG. CO.**
1161 RUGGLES ST GRAND PRAIRIE, TX 75050
972-641-8444 * 1-800-222-5644 * fax 972-641-8488
www.dallasspecialty.com