

DS1200R

DALLAS SPECIALTY RECTANGULAR METER BOX - 17" WIDE x 12" LONG x 12" DEEP

PALLET QTY / 72pc

MFG'D IN THE USA BY DALLAS SPECIALTY & MFG CO

BOX

MODEL# DS1200R ASSEMBLED ON DS1200B WITH DS1200RL LID

ACCOMMODATES FLUSH OR OVERLAPPING STYLE DS LIDS

DIMENSIONS: 12" Deep Top 17-1/8"x11-7/8" od
Base 21"x16-5/8" od

MATERIAL: POLYPROPYLENE

BOX PIPE SLOTS/OUTLETS: SINGLE SLOT/OUTLETS - 2-1/4" Wide x 3-1/2" Tall

BOX ADDITIONS/COMPATIBILITY: DUAL OUTLET BOX, NO OUTLET BOX
AND/OR DS600EXT 6" EXTENSION BOX WITH OR WITHOUT OUTLETS

LID

MODEL# DS1200R ASSEMBLED WITH #DS1200RL METER READER LID ON DALLAS
SPECIALTY PART #DS1200B METER BOX/BODY - DS1200RL MADE FOR ASSEMBLY ON
DS1200B OR DS600EXT BODY

DIMENSIONS: 15-3/8"x10-1/8" od x 1-3/4" thick / Rectangle Lid

MATERIAL: POLYPROPYLENE

COLOR: BLACK - INTENDED FOR YARDS, PLANTERS, PARKWAYS, GRASS AREAS,
GOLF COURSES, OR METER/VALVE HOUSING AND ACCESS APPLICATIONS

FIT: FLUSH STYLE LID WITH READER DOOR - FITS TIGHT WITH SNAP DOWN TABS,
REMOVES EASILY USING 1" DIAMETER FINGER HOLE

MARKINGS: STANDARD MFG MARKINGS & IDENTIFICATION
CUSTOM MARKINGS AVAILABLE & LOGOS

LID ADDITION/OPTIONS: MULTIPLE LID COLOR OPTIONS, OVERLAPPING
STYLE LID AVAILABLE, INSTALLATION OF SOCKET/BOLT LOCK, 1" OR 2" TOUCH
READ HOLE AVAILABLE AND/OR AMR BRACKET (ONLY AVAILABLE ON OVER-
LAPPING LID)



PROPERTIES / TEST VALUES

Tensile Strength: 3480 PSI

Density: 0.918

Durometer Shore D0.825

Flexural Strength: 255-300 PSI

Minimal Wall Dim: 0.250"

Deflection Temp: 200 F at 66 psi

IZOD IN 23C: 1.05 ft lbs/in

IZOD IUN 18C: 5.3 ft lbs/in



DALLAS SPECIALTY & MFG. CO.

1161 RUGGLES ST GRAND PRAIRIE, TX 75050

972-641-8444 * 1-800-222-5644 * fax 972-641-8488

www.dallasspecialty.com