


SPECIFICATIONS

Dallas Specialty Flexible Pipe Coupling for Sewer & Drain connections



Part# **DS56-1515**

FITS: 15"Cast Iron, PVC, ST Pipe x 15"Cast Iron, PVC, ST Pipe
Fits size range 14.80-16.10" Pipe OD's x 14.80-16.10" Pipe OD's



Coupling Made to ID Specifications



"A" (ID)	"B" (ID)	"C" WIDTH
15.40" id	15.40" id	6.50"

Minimum - Maximum Temperature	-30°F to 140°F
Shielded Coupling Weight	4.5#
Pressure Rating	No Pressure / for drainage
Material / Resins	Flexible PVC - 55-60
Coupling Wall Thickness	3/8"

Install Torque	60in-lb torque
Meets ASTM	C1173 / D5926
Case Qty / Case Wgt	2pc/cs - 10#/cs
Band Series	301 Series Stainless Steel
Clamps	(2) DS-248

Coupling

- Meeting Material Requirements of IPC[®] / IRC[®]
- cUPC[®] Meets Canadian Standards
- ASTM C-1173 D-5926
- Sporadic Temperature Rating 140°
- Maximum Test Pressure 4.3 PSI
- Made in USA



Clamps

- (2) DS-248 - 1/2" Wide / 301SS Stainless Steel Bands
- Installation Torque: 60in-lb
- Clamp Screw: 5/16" Hex Head / AISI 301SS
- Clamp Housing: All Stainless / AISI 304SS
- Meets Requirements: SAE J1670



Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ± 3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS
SPECIALTY
& MFG CO.**

1161 RUGGLES ST. GRAND PRAIRIE, TX 75050

P: 972-641-8444 • 800-222-5644 • F: 972-641-8488

Email: ds@dalspc.com • www.dallasspecialty.com