



SPECIFICATIONS

Large Diameter Flexible Pipe Coupling for Sewer & Drain applications



Part# **DS56-3030**

FITS: 30" Cast Iron, Steel or PVC Pipe x 30" Cast Iron, Steel or PVC Pipe
Fits size range 29.60-30.30" Pipe OD's x 29.60-30.30" Pipe OD's



Coupling Made to ID Specifications

"A" (ID)	"B" (ID)	"C" WIDTH
30.00" id	30.00" id	8.00"





Minimum - Maximum Temperature	-30°F to 140°F
Coupling Weight	15#
Pressure Rating	No Pressure / for drainage
Material / Resins	Rubber
Coupling Wall Thickness	1/2" Thickness

Install Torque	60in-lb torque
Meets ASTM	C1173 / D5926
Case Quantity	1 pc
Band Series	301 Series Stainless Steel
Clamps	(8) DS-270 Bands

Coupling

- Meeting Material Requirements of IPC[®] / IRC[®]
- cUPC[®] Meets Canadian Standards
- ASTM C-1173 D-5926 
- Sporadic Temperature Rating 140°
- Maximum Test Pressure 4.3 PSI
- Made in the USA

Clamps/Bands

- (8) DS-270 - 1/2" Wide / 301SS Stainless Steel Bands
- Installation Torque: 60in-lb
- Clamp Screw: 5/16" Hex Head / AISI 301SS
- Clamp Housing: All Stainless / AISI 304SS
- Meets Requirements: SAE J1670 
- HD Stainless Steel Shield #DS-SR-53 .012 Thickness  5/16" HH 60lbTq

Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ± 3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS
SPECIALTY
& MFG CO.**

1161 RUGGLE ST. GRAND PRAIRIE, TX 75050

P: 972-641-8444 • 800-222-5644 • F: 972-641-8488

Email: ds@dalspc.com • www.dallasspecialty.com