


# SPECIFICATIONS

# Shielded Pipe Coupling

for Sewer & Drain applications

Part# **DS56-88SR**

FITS: 8"Cast Iron / PVC Pipe x 8"Cast Iron / PVC Pipe  
Fits size range 8.25"-8.75" Pipe OD's x 8.25"-8.75" Pipe OD's



Coupling Made to ID Specifications

"A" (ID)	"B" (ID)	"C" WIDTH
8.50"	8.50"	6.00"



Picture may not be actual part, for reference only to show style of coupling & banding


Minimum - Maximum Temperature	-30°F to 140°F
Shielded Cplg Weight	3.10#each
Pressure Rating	No Pressure / for drainage
Coupling Material/Resins	Flexible PVC (55-60Dur)
Coupling Wall Thickness	3/8"

Install Torque	60in-lb torque
Meets ASTM	C1173 / D5926
Quantity/Case & Weight	12 pc/case - 43#/cs
Band Series	301 Series Stainless Steel
Clamps/Bands	Worm Gear Style

## Coupling

- Meeting Material Requirements of IPC<sup>®</sup> / IRC<sup>®</sup>
- cUPC<sup>®</sup> Meets Canadian Standards
- ASTM C-1173 D-5926 
- Sporadic Temperature Rating 140°
- Maximum Test Pressure 4.3 PSI

## Clamps/Shield

- (2) DS-152 - 1/2" Wide / 301SS Stainless Steel Bands - weight .142#ea
- Installation Torque: 60in-lb
- Clamp Screw: 5/16" Hex Head / AISI 301SS
- Clamp Housing: All Stainless / AISI 304SS
- Meets Requirements: SAE J1670 
- HD Stainless Steel Shield #DS-SR-46 .012 Thickness 5/16" HH 60lbTq
- Shear - DS Part #DS-SR-34 - .90#each

Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, $\pm 3$ 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS  
SPECIALTY  
& MFG CO.**

1161 RUGGLE ST. GRAND PRAIRIE, TX 75050

P: 972-641-8444 • 800-222-5644 • F: 972-641-8488

Email: [ds@dalspc.com](mailto:ds@dalspc.com) • [www.dallasspecialty.com](http://www.dallasspecialty.com)