

# SPECIFICATIONS

# Flexible PVC Pipe Coupling


Connector for Sewer & Drain applications

Part# **DS58-150**

FITS: 1-1/2" Cast Iron, ABS/PVC, Plastic Pipe x 1-1/2" Copper Pipe



Coupling pictured may not be exact part as listed here, for reference only



Coupling Made to Inside Dimension Specifications

"A" (ID)	"B" (ID)	"C" WIDTH
1.90" id	1.625" id	3.50" width

Maximum Temperature	140° F degrees
Minimum Temperature	-30° F degrees
Pressure Rating	4.3lbs maximum PSI / Non-Pressure
Coupling Wall Thickness	3/8" (0.375")
Material	Phthalates free - High-Quality

Install Torque	60in-lb torque
Meets ASTM Standards	C1173 / D5926
Case Quantity	54 per case
Clamp Series	301SS Series Stainless
Worm Gear Bands	(2) Worm Gear SS Bands

## Coupling

- Manufactured in the USA
- Meeting Material Requirements of IPC<sup>®</sup>/IRC<sup>®</sup>
- cUPC<sup>®</sup> Meets Canadian Standards
- Meets ASTM Standards: C-1173 & D-5926
- Maximum Sporadic Temp Rating 140° F



## Stainless Steel Clamps

- Clamp: 3/8" Wide / AISI 301SS
- Clamp Torque: 60in-lb Install Torque
- Screw: 5/16" Hex Head / AISI 301SS
- Housing: All Stainless / AISI 304SS
- Meets Requirements: SAE J1670



Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ±3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS  
SPECIALTY  
& MFG CO.**

1161 RUGGLE ST. GRAND PRAIRIE, TX 75050

P: 972-641-8444 • 800-222-5644 • F: 972-641-8488

Email: ds@dalspc.com • [www.dallasspecialty.com](http://www.dallasspecialty.com)