

SPECIFICATIONS


Flexible PVC Pipe Coupling

for Sewer & Drain connections



Part# **DS70-1010**

FITS: 10" ADS Corrugated HDPE x 10" Cast Iron/PVC Pipe accommodates pipe size range 11.00 - 11.50" OD's x 10.30-10.80" OD's



Coupling Made to ID Specifications



"A" (ID)	"B" (ID)	"C" WIDTH
11.20"	10.60"	6.50"

Maximum Temperature	140°degree F
Minimum Temperature	-30°degree F
Pressure Rating	Max. Test Pressure 4.3PSI
Material / Resins	Flexible PVC - 55/60
Coupling Wall Thickness	1/2" Thickness

Install Torque	60in-lb torque
Meets ASTM	C1173 / D5926
Quantity/Case	2 pc/case
Band Series	301 Series Stainless
Clamps/Bands	Worm Gear Style

Coupling

- Meeting Material Requirements of IPC[®] / IRC[®]
- cUPC[®] Meets Canadian Standards
- ASTM C-1173 / D-5926 
- Sporadic Temperature Rating - 140°F
- Maximum Test Pressure 4.3 PSI

Stainless Steel Clamps

- (2) All Stainless Clamps - 1/2" Wide/ 301SS Stainless Steel
- Installation Torque: 60in-lb
- Screw: 5/16" Hex Head / AISI 301SS
- Clamp Housing: All Stainless / AISI 304SS
- Meets Requirements: SAE J1670 

Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ± 3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS
SPECIALTY
& MFG CO.**

1161 RUGGLE ST. GRAND PRAIRIE, TX 75050

P: 972-641-8444 • 800-222-5644 • F: 972-641-8488

Email: ds@dalspc.com • www.dallasspecialty.com