GAS BALL VALVES

HEAVY DUTY FORGED BRASS BODY WITH CHROME PLATED BRASS BALL

- HANDLES ENSURE ON/OFF OPERATING EVEN IN COM-PACT INSTALLATIONS & SPACES
- QUARTER-TURN OPERATION FOR EASY ON/OFF
 FLOW CONTROL
- FULL FLOW OPERATION, FULL PORT DESIGN
- APPROVED FOR INDOOR OR OUTDOOR USE
- SIZES: 1/2", 3/4" OR 1" FOR CONNECTING FIP x FIP
- MAXIMUM OPERATING PRESSURE: 5PSI MAX
- OPERATING TEMPERATURE: 40°-180°F MAX
- UL LISTED / CGA (CANADIAN GAS ASSOCIATION) CERTIFIED
 CSA LISTED

YELLOW HANDLE GAS BALL VALVES

Dallas Specialty Part#	SIZE	BAG / CASE
DSCSA12GV	1/2"FIP x 1/2"FIP	12/BG - 120/CS
DSCSA34GV	3/4"FIP x 3/4"FIP	10/BG - 100/CS
DSCSA1GV	1"FIP x 1"FIP	6/BG - 96/CS

The National Fuel Gas Code requires a gas shut-off valve installed upstream, within "easy reach" or 6'feet of the gas appliance





DALLAS SPECIALTY & MFG. CO.

1161 RUGGLES ST GRAND PRAIRIE, TX 75050 972-641-8444 * 1-800-222-5644 * fax 972-641-8488

www.dallasspecialty.com