

SPECIFICATIONS

Shielded Flexible Pipe Coupling

for Sewer & Drainage applications




Part# **DS06-128SR**

FITS: 12" Concrete Pipe x 8" Cast Iron, PVC or STEEL Pipe

Accommodates size range 14.80-15.85" Pipe OD's x 8.25-8.60" Pipe OD's

Flexible PVC insert bushings used to accommodate size reduction.

Picture is for reference only, may not be actual part as listed



Coupling Made to ID Specifications

"A" (ID)	"B" (ID)	"C" WIDTH
15.40" id	8.50" id	6.50"



Minimum - Maximum Temperature	-30°F to 140°F
Shielded Coupling Weight	7.5#
Pressure Rating	No Pressure / for drainage
Material / Resins	Flexible PVC - 55-60
Coupling Wall Thickness	3/8"

Install Torque	60in-lb torque
Meets ASTM	C1173 / D5926
Case Qty / Case Wgt	2pc/cs - 15#/cs
Band Series	301 Series Stainless Steel
Clamps & Shield	(2) DS-270 & (1) DS-SR-53

Coupling

- Meeting Material Requirements of IPC[®] / IRC[®]
- cUPC[®] Meets Canadian Standards
- ASTM C-1173 D-5926 
- Sporadic Temperature Rating 140°
- Maximum Test Pressure 4.3 PSI

Clamps/Shield

- (2) DS-270 - 1/2" Wide / 301SS Stainless Steel Bands
- Installation Torque: 60in-lb
- Clamp Screw: 5/16" Hex Head / AISI 301SS
- Clamp Housing: All Stainless / AISI 304SS
- Meets Requirements: SAE J1670 
- HD Stainless Steel Shield #DS-SR-46 .012 Thickness 5/16" HH 60lbTq

Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ± 3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS
SPECIALTY
& MFG CO.**

1161 RUGGLE ST. GRAND PRAIRIE, TX 75050

P: 972-641-8444 • 800-222-5644 • F: 972-641-8488

Email: ds@dalspc.com • www.dallasspecialty.com