

# DS1200IP

**DALLAS SPECIALTY** STANDARD RECTANGULAR VALVE/METER BOX

17" WIDE x 12" LONG x 12" DEPTH

PALLET QTY / 72pc

MFG'D IN THE USA

## BOX

**MODEL#** DS1200B ASSEMBLED WITH DS1200IPL (SOLID PURPLE LID)

BOX ACCOMMODATES FLUSH OR OVERLAPPING STYLE DS LIDS

**MATERIAL:** HD POLYPROPYLENE

**OUTLETS:** SINGLE 2-3/4" PIPE SLOTS

**DIMENSIONS:** TOP 17-1/8" x 11-7/8" OD  
BASE 21" x 16-5/8" OD x 1/4" THICK

**SPECS:** ASTM

**BOX ADDITIONS/COMPATIBILITY:** #DS600EXT 6" EXTENSION BOX

## LID

**MODEL#** DS1200IPL ASSEMBLED ON DS SINGLE OUTLET VALVE/METER BOX  
FOR ASSEMBLY ON DS1200B BOXES OR DS600EXT EXTENSION BOX

**MATERIAL:** HD POLYPROPYLENE

**LID DIMENSIONS:** FLUSH FIT 15-3/8" x 10-1/8" OD

**COLOR:** PURPLE (USED IN YARDS, PLANTERS, PARKWAYS, GRASSY AREAS, GOLF COURSES, AND/OR VALVE & IRRIGATION CONTROLS APPLICATIONS)

**FIT:** FLUSH STYLE / FITS TIGHT WITH SNAP DOWN TABS

**LID REMOVAL:** USE 1" HOLE ON TOP OF LID

**MARKINGS:** RECLAIMED WATER - STANDARD MFG MARKINGS & IDENTIFICATION  
CUSTOM MARKINGS AVAILABLE & LOGOS

**SPECS:** ASTM

**LID ADDITION OPTIONS:** 2" TOUCH READ HOLE, AND/OR AMR BRACKET ATTACHMENT, AND/OR SOCKET BOLT LOCK, OR READER DOOR LIDS AVAILABLE



### PROPERTIES / TEST VALUES

Tensile Strength: 3480 PSI

Density: 0.918

Durometer Shore D0.825

Flexural Strength: 255-300 PSI

Minimal Wall Dim: 0.250"

Deflection Temp: 200 F at 66 psi

IZOD IN 23C: 1.05 ft lbs/in

IZOD IUN 18C: 5.3 ft lbs/in



**ds**® **DALLAS SPECIALTY & MFG. CO.**  
1161 RUGGLES ST GRAND PRAIRIE, TX 75050  
972-641-8444 \* 1-800-222-5644 \* fax 972-641-8488  
[www.dallasspecialty.com](http://www.dallasspecialty.com)