

DS1200IS

DALLAS SPECIALTY RECTANGULAR VALVE BOX - 17" x 12" x 12"
PALLET QTY / 72pc

MFG'D IN THE USA

BOX

MODEL# DS1200B ASSEMBLED WITH DS1200ISL

ACCOMODATES FLUSH OR OVERLAPPING STYLE DS LIDS

MATERIAL: HD POLYPROPYLENE

BOX DIMENSIONS: TOP - 17-1/8"x11-7/8"OD
BASE - 21"x16-5/8"OD x 1/4" THICK

OUTLETS: SINGLE OUTLET 2-3/4"

SPECS: ASTM

BOX ADDITIONS/COMPATIBILITY: DS600EXT 6"EXTENSION BOX

LID

MODEL# DS1200ISL LID ASSEMBLED ON DALLAS SPECIALTY BODY
#DS1200B (SINGLE OUTLET BOX BODY) - LID CAN BE USED FOR ASSEM-
BLY ON DS1200B, DS1200B2 AND/OR DS600EXT BODIES

MATERIAL: HD POLYPROPYLENE

LID DIMENSIONS/FLUSH FIT: 15-3/8" x 10-1/8"OD

COLOR: GREEN (FOR YARDS, PLANTERS, PARKWAYS, GRASS AREAS,
GOLF COURSES, OR IRRIGATION VALVE APPLICATIONS)

FIT: FLUSH STYLE / FITS TIGHT WITH SNAP DOWN TABS

REMOVE LID USING 1"HOLE ON TOP OF LID

MARKINGS: LID IS MARKED "SEWER" - STANDARD MFG MARKINGS &
IDENTIFICATION CUSTOM MARKINGS AVAILABLE & LOGOS

SPECS: ASTM

LID ADDITION OPTIONS: 2"TOUCH READ HOLE, AND/OR AMR BRACKET



PROPERTIES / TEST VALUES

Tensile Strength: 3480 PSI

Density: 0.918

Durometer Shore D0.825

Flexural Strength: 255-300 PSI

Minimal Wall Dim: 0.250"

Deflection Temp: 200 F at 66 psi

IZOD IN 23C: 1.05 ft lbs/in

IZOD IUN 18C: 5.3 ft lbs/in



ds® **DALLAS SPECIALTY & MFG. CO.**
1161 RUGGLES ST GRAND PRAIRIE, TX 75050
972-641-8444 * 1-800-222-5644 * fax 972-641-8488
www.dallasspecialty.com