

DS1500I

DALLAS SPECIALTY RECTANGULAR JUMBO VALVE BOX -
21" WIDE x 15" LONG x 12" DEEP PALLET QTY / 32pc MFG'D IN USA

BOX

MODEL# DS1500B BODY IS ASSEMBLED WITH DS1500IL GREEN PLASTIC IRRIGATION FLUSH STYLE LID TO MAKE #DS1500I

DIMENSIONS: 12" Deep Box

Top Dimensions 20-5/8" ID (22-1/2" OD) x 14-7/8" ID (16-3/4" OD)

Base Dimensions 23-3/4" ID (25-1/2" OD) x 18" ID (19-1/2" OD)

MATERIAL: POLYPROPYLENE

OUTLETS: SINGLE PIPE OUTLET SIZED 2-1/2" - BOX IS AVAILABLE WITH DUAL OUTLETS TO ACCOMMODATE DOUBLE CHECK VALVE INSTALLATIONS

BOX ADDITIONS AVAILABLE: DUAL OUTLETS, EXTENSION BOX PART NUMBER #DS750E TO GIVE 6" RISE AND CAN ALSO ACCOMMODATE MULTIPLE EXTENSIONS FOR FURTHER RISE

LID

MODEL# DS1500IL - SOLID PLASTIC GREEN SOLID LID - SNAPS-IN (FITS FLUSH) ASSEMBLED ON DS1500B BOX BODY TO MAKE DALLAS SPECIALTY JUMBO BOX #DS1500I

USAGE: FOR ASSEMBLY ON DS1500B OR DS750 BOX/BODIES

LID: FLUSH GREEN IRRIGATION SNAP-DOWN LID

Dimensions: 20-5/8" OD x 14-7/8" OD x 1-1/2" thick

MATERIAL: POLYPROPYLENE

LID COLOR: GREEN

FIT: FLUSH STYLE / FITS TIGHT WITH SNAP DOWN TABS

REMOVE LID USING 1" HOLE ON TOP OF LID

MARKINGS: STANDARD MFG MARKINGS & IDENTIFICATION

LID ADDITION OPTIONS TO DS1500IL: 2" TOUCH READ HOLE, BOX ALSO ACCOMMODATES DS1500CIL (SOLID CAST IRON LID FOR LIGHT SIDEWALK/DRIVEWAY TRAFFIC) AND MULTIPLE OTHER LID VARIETIES



PROPERTIES / TEST VALUES

Tensile Strength: 3480 PSI

Density: 0.918

Durometer Shore D0.825

Flexural Strength: 255-300 PSI

Minimal Wall Dim: 0.250"

Deflection Temp: 200 F at 66 psi

IZOD IN 23C: 1.05 ft lbs/in

IZOD IUN 18C: 5.3 ft lbs/in



ds® **DALLAS SPECIALTY & MFG. CO.**
1161 RUGGLES ST GRAND PRAIRIE, TX 75050
972-641-8444 * 1-800-222-5644 * fax 972-641-8488

www.dallasspecialty.com