

DS1500SCI

DALLAS SPECIALTY RECTANGULAR JUMBO VALVE BOX - 21" WIDE x 15" LONG x 12" DEEP
PALLET QTY / 32pc

MFG'D IN THE USA

BOX

MODEL# DS1500B BODY IS ASSEMBLED WITH DS1500SCIL BLACK SOLID CAST IRON LID TO MAKE #DS1500SCI

DIMENSIONS: 12" Deep Box - Top Dimensions 21-1/4" od x 15-1/2" od
Base Dimensions 25-7/8" od x 19-3/4" od

MATERIAL: POLYPROPYLENE

OUTLETS: SINGLE PIPE OUTLET SIZED 2-3/4" - BOX IS AVAILABLE WITH DUAL OUTLETS TO ACCOMMODATE DOUBLE CHECK VALVE INSTALLATIONS

BOX ADDITIONS: DUAL OUTLETS, EXTENSION BOX PART NUMBER #DS750EXT AVAILABLE FOR 6" RISE AND CAN ACCOMMODATE MULTIPLE EXTENSIONS FOR FURTHER RISE

LID

MODEL# DS1500SCIL — SOLID CAST IRON BLACK LID FITS FLUSH - ASSEMBLED ON DS1500B BOX BODY TO MAKE DALLAS SPECIALTY JUMBO BOX #DS1500SCI ASSEMBLED PART NUMBER

USAGE: FOR ASSEMBLY ON DS1500B OR DS750 BOX/BODIES

DIMENSIONS: Flush Irrigation Lid: 19-3/4" x 13-7/8" od x 1-1/2" height

MATERIAL: POLYPROPYLENE

LID COLOR: BLACK

FIT: FLUSH STYLE / SOLID CAST IRON FOR LIGHT TRAFFIC AREAS, SIDEWALKS & DRIVEWAYS

MARKINGS: STANDARD MFG MARKINGS AND IDENTIFICATION

ADDITION LID OPTIONS TO FIT DS1500B BODY: STANDARD PLASTIC FLUSH FIT SOLID LID AVAILABLE WITH OR WITHOUT "TOUCH READ HOLE(S)". AVAILABLE IN READER STYLE PLASTIC LID FOR METERS AND MANY OTHER CONFIGURATIONS. CONTACT US AT 800-222-5644 FOR OPTIONS. MULTIPLE LID COLORS AVAILABLE



PROPERTIES / TEST VALUES

Tensile Strength: 3480 PSI

Density: 0.918

Durometer Shore D0.825

Flexural Strength: 255-300 PSI

Minimal Wall Dim: 0.250"

Deflection Temp: 200 F at 66 psi

IZOD IN 23C: 1.05 ft lbs/in

IZOD IUN 18C: 5.3 ft lbs/in



ds® **DALLAS SPECIALTY & MFG. CO.**
1161 RUGGLES ST GRAND PRAIRIE, TX 75050
972-641-8444 * 1-800-222-5644 * fax 972-641-8488
www.dallasspecialty.com