

DS600EXT

DALLAS SPECIALTY DS1200 SERIES 6" EXTENSION BOX

RECTANGULAR VALVE BOX EXTENSION—FOR DS1200 SERIES BOXES

PALLET QTY 48pc

MFG'D IN THE USA

TOP ID: 15-1/2"W x 10-1/4"L TOP OD: 17"W x 11-5/8"L

DEPTH: 7"

BASE ID: 17"W x 12"L BASE OD: 18-1/4" x 14"L

THICKNESS: 5/8"

BOX/OPTIONS

MODEL # DS600EXT EXTENSION BODY DESIGNED TO FIT DALLAS SPECIALTY DS1200 SERIES VALVE & METER BOXES – TO BE ASSEMBLED ON TOP OF DS1200 SERIES BODIES

ACCOMODATES FLUSH OR OVERLAPPING STYLE DALLAS SPECIALTY DS1200 LIDS OF ALL STYLES
(REF. WWW.DALSPC.COM FOR LID OPTIONS)

MATERIAL: HIGH DENSITY POLYPROPYLENE

BODY OPTIONS: SINGLE PIPE OUTLET / 2-3/4" - STANDARD EXTENSION BOX DESIGNED WITHOUT PIPE OUTLETS, AVAILABLE WITH SINGLE PIPE OUTLETS #DS600B

SPECS: MEETS ASTM STANDARDS

LID / OPTIONS

ALL DALLAS SPEICALTY DS1200 LIDS MODEL# DS1200 LID FIT #DS600 EXTENSION BOXES AND ARE ALSO ABLE TO BE PURCHASED ASSEMBLED WITH ANY DS1200 LID (SUCH AS: DS1200IL, DS1200RL, DS1200IBL, DS1200SCIL LIDS, ETC..)

MATERIAL: HIGH DENSITY POLYPROPYLENE

AVAILABLE LID OPTIONS: MULTIPLE COLORS FOR IDENTIFYING BOX USAGE, AND USAGES. USED IN YARDS, PLANTERS, PARKWAYS, GRASSY AREAS, GOLF COURSES, AND/OR VALVE & IRRIGATION CONTROLS APPLICATIONS

FIT: FLUSH STYLE / FITS TIGHT WITH SNAP DOWN TABS

LID REMOVAL: USING 1"HOLE ON TOP OF LID

MARKINGS: STANDARD MFG MARKINGS & IDENTIFICATION ON STANDARD LIDS OR CUSTOM MARKINGS AVAILABLE

SPECS: MEETS ASTM STANDARDS



PROPERTIES / TEST VALUES

Tensile Strength: 3480 PSI

Density: 0.918

Durometer Shore D0.825

Flexural Strength: 255-300 PSI

Minimal Wall Dim: 0.250"

Deflection Temp: 200 F at 66 psi

IZOD IN 23C: 1.05 ft lbs/in

IZOD IUN 18C: 5.3 ft lbs/in