

SPECIFICATIONS

Eccentric Shielded Pipe Coupling


for Sewer & Drain connections

Part# **DS02-86ESR**

FITS: 8"Clay Pipe x 6"Cast Iron/PVC Pipe

Fits size range 9.40-9.90" Pipe OD's x 6.45-6.55" Pipe OD's

Dallas Specialty DS02SR Series Shielded Pipe Couplings fit a variety of piping systems such as: Clay Pipe and other similar sized piping systems with similar pipe od's to Cast Iron/PVC Pipe or other similar sized piping systems. Limited sizes available in Eccentric Style, providing even-flow drainage. See sizing chart for our extensive line of sizes available.



Picture may not be actual part, for reference only to show style of coupling & banding. Eccentric Style Couplings are assembled with Flexible PVC Insert Bushing(s) to attain reduced sizes

Coupling Made to ID Specifications



"A" (ID)	"B" (ID)	"C" WIDTH
9.65"	6.50"	6.00"

Minimum - Maximum Temperature	-30°F to 140°F
Shielded Coupling Weight	9.20#each
Pressure Rating	No Pressure / for drainage
Coupling Material/Resins	Flexible PVC (55-60Dur)
Coupling Wall Thickness	3/8"

Install Torque	60in-lb torque
Meets ASTM	C1173 / D5926
Quantity/Case	4 pc/case
Band Series	301 Series Stainless Steel
Clamps/Bands	Worm Gear Style

Coupling

- Meeting Material Requirements of IPC®/ IRC®
- cUPC® Meets Canadian Standards
- ASTM C-1173 D-5926 
- Sporadic Temperature Rating 140°
- Maximum Test Pressure 4.3 PSI

Clamps/Shield

- (2) DS-152 - 1/2" Wide/ 301SS Stainless Steel Bands
- Installation Torque: 60in-lb
- Clamp Screw: 5/16" Hex Head / AISI 301SS
- Clamp Housing: All Stainless / AISI 304SS
- Meets Requirements: SAE J1670 
- HD Stainless Steel Shield #DS-SR-46 - .012 Thickness 5/16" HH 60lbTq

Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ± 3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS
SPECIALTY
& MFG CO.**

1161 RUGGLES ST. GRAND PRAIRIE, TX 75050

P: 972-641-8444 • 800-222-5644 • F: 972-641-8488

Email: ds@dalspc.com • www.dallasspecialty.com