

SPECIFICATIONS

Dallas Specialty Shielded Flexible Pipe Coupling for Sewer & Drain connections

Part# **DS58-88SR**


FITS: 8" Cast Iron/ PVC Pipe x 8" Copper Pipe

Fits pipe size range 8.20-8.75" Pipe OD's x 8.00-8.20" Pipe OD's



Picture may not be actual part, for reference only of part or similar part

Reducing sized shielded couplings
assembled with (1) or more flexible
insert bushings to accommodate size
reduction



Coupling Made to ID Specifications

"A" (ID)	"B" (ID)	"C" WIDTH
8.50"	8.125"	6.00"



Minimum - Maximum Temperature	-30°F to 140°F
Shielded Cplg Weight	5.35#each
Pressure Rating	No Pressure / for drainage
Coupling Material/Resins	Flexible PVC (55-60Dur)
Coupling Wall Thickness	3/8"

Install Torque	60in-lb torque
Meets ASTM	C1173 / D5926
Quantity/Case	4 pc/case
Band Series	301 Series Stainless Steel
Clamps/Bands	Worm Gear Style

Coupling

- Meeting Material Requirements of IPC[®] / IRC[®]
- cUPC[®] Meets Canadian Standards
- ASTM C-1173 D-5926 
- Sporadic Temperature Rating 140°
- Maximum Test Pressure 4.3 PSI
- High Quality Flexible PVC Phthalates Free Resins

Clamps/Shield

- (2) DS-128 - 1/2" Wide SS Clamps 301SS Stainless Steel
- Installation Torque: 60in-lb
- Worm Gear Clamp Screw: 5/16" Hex Head / AISI 301SS
- Worm Gear Clamp Housing: All Stainless / AISI 304SS
- Meets Requirements: SAE J1670 
- HD Stainless Steel Shield #DS-SR-34 .012 Thickness 5/16" HH 60lbTq
- HD Stainless Steel Shield - DS Part #DS-SR-34

Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ± 3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb C°	-40	-40	D-746
Tear Strength	150in-lb	150in-lb	D-746



**DALLAS
SPECIALTY
& MFG CO.**

1161 RUGGLE ST. GRAND PRAIRIE, TX 75050

P: 972-641-8444 • 800-222-5644 • F: 972-641-8488

Email: ds@dalspc.com • www.dallasspecialty.com